

Stunning Colors and Highly Flexible Projection



PT-DZ870	PT-DW830	PT-DX100
8,500 lm	8,500 lm	10,000 lm
WUXGA (1920 × 1200)	WXGA (1280 × 800)	XGA (1024 × 768)

NOTE: Models without lenses (PT-DZ870L/DW830L/DX100L) are also available. The specifications are the same as those of the PT-DZ870/DW830/DX100 respectively. All models are offered in a black (PT-DZ870K/DZ870LK/DW830K/DW830LK/DX100K/DX100LK) or white (PT-DZ870W/DZ870LW/DW830W/DW830LW/DX100W/DX100LW) cabinet.

Vivid Picture Quality with High Brightness

- Unique lamp drive systems have helped to make the body compact, while providing a high 8,500 lm*¹ of brightness.
- Full-HD-ready WUXGA resolution.*²
- The dynamic iris achieves a high contrast ratio of 10,000:1.
- Panasonic's proprietary Dynamic RGB Booster achieves high image quality with excellent color reproduction and brightness.
- Active 3D projection capability.
- Detail Clarity Processor 3 brings depth and clarity to details.
- Waveform Monitor for easy and precise calibration.
- System Daylight View 2 enhances color perception with no need to turn off the lights.
- The DICOM Simulation mode*³
- Rec. 709 mode for HDTV projection.
- Full 10-bit signal processing.
- Advanced technologies for excellent image quality: 3D color management system, HD IP conversion, digital noise reduction, dynamic sharpness control.

Easy Maintenance and Superior Reliability

- A dust-resistant optical block keeps images crisp and vivid by preventing dust entry.
- A new cooling mechanism with a heat dissipating block utilizing a heat pipe.
- Panasonic's unique Dual Lamp System eliminates a sudden interruption if a lamp should fail (in dual-lamp operation mode).
- The Lamp Relay mode also operates the lamps alternately to enable 24/7 projection.
- New lamp and new drive system improve reliability and achieve long life.
- Lamp replacement cycle of up to 3,000 hours*⁵
- Easy lamp replacement from the rear.
- Optional Smoke-Resistant Filter ET-SFD120 available.

System Integration Flexibility

- DIGITAL LINK allows HDMI, uncompressed HD videos, audio, and control signals through a single Cat5e/6 LAN cable.
- Compatible with optional ET-YFB100G or other switchers.*⁶

- The Geometric Adjustment function.*⁷
- Optional "Geometry Manager Pro Ver. 1.1" for more flexible geometric adjustment and modified masking functions.*⁷
- The Multi-Screen Support System: Edge blending, color matching and multi-screen processor.
- Flexible vertical 360 degree installation, lens-centered design, horizontal/vertical-lens shift and a wide range of optional lenses.
- Portrait mode projection available later on.*⁸
- Mechanical shutter with fade in/out effect.
- The Multi-Unit Brightness Control function.
- Abundant terminals, including SDI (3G support)*⁷, DVI-D, HDMI and 3D timing signal in/out.

*¹ 10,000 lm for the PT-DX100. *² For the PT-DZ870 only. *³ This product is not a medical instrument. Do not use it for actual medical diagnosis. *⁴ The operating temperature range is 0 °C to 40 °C (32 °F to 104 °F) when the HIGH ALTITUDE MODE is set to ON (for altitudes from 1,400 m to 2,700 m (4,593 ft to 8,858 ft) above sea level). Also, if the ambient temperature exceeds 40 °C (104 °F) (35 °C (95 °F) in HIGH ALTITUDE MODE) when the projector is being used with LAMP SELECT set to DUAL and LAMP POWER set to NORMAL, the light output may be reduced approximately 20% to protect the projector. *⁵ With the LAMP POWER set to NORMAL mode. The usage environment affects the lamp replacement cycle. *⁶ Crestron's DigitalMedia 8G+™, Extron's XTP Systems and AMX's Enova DVX. *⁷ For the PT-DZ870 only. *⁸ Optional lamp units for portrait projection required.

Specifications (Tentative)

P R E L I M I N A R Y
As of January 2013

Model	PT-DZ870/DZ870L	PT-DW830/DW830L	PT-DX100/DX100L	
Power supply	120 V–240 V AC, 12 A, 50/60 Hz			
Power consumption	1,130 W (1,180 VA at 120 V) (0.3 W with STANDBY MODE set to ECO,* ⁸ 4 W with STANDBY MODE set to NORMAL. Both with fan stopped.)			
DLP™ chip	17.0 mm (0.67 in) diagonal (16:10) DLP™ chip × 1, DLP™ projection system 2,304,000 (1,920 × 1,200) pixels	16.5 mm (0.65 in) diagonal (16:10) DLP™ chip × 1, DLP™ projection system 1,024,000 (1,280 × 800) pixels	17.8 mm (0.7 in) diagonal (4:3) DLP™ chip × 1, DLP™ projection system 786,432 (1,024 × 768) pixels	
Lens	PT-DZ870/DW830/DX100 Powered zoom (1.7–2.4:1), powered focus F 1.7–1.9, f 25.6 – 35.7 mm	PT-DZ870L/DW830L/DX100L Optional powered zoom/focus lenses and fixed-focus lens		
Lamp	420 W UHM lamp × 2			
Screen size (diagonal)	1.27–15.24 m (50–600 in)* ⁹ (16:10)	1.27–15.24 m (50–600 in)* ⁹ (16:10)	1.27–15.24 m (50–600 in)* ⁹ (4:3)	
Brightness* ¹⁰	8,500 lm (dual-lamp, LAMP MODE: NORMAL)		10,000 lm (dual-lamp, LAMP MODE: NORMAL)	
Center-to-corner uniformity* ¹⁰	90 %			
Contrast* ¹⁰	10,000:1 (full on/off, with DYNAMIC IRIS set to ON)			
Resolution	1,920 × 1,200 pixels	1,280 × 800 pixels* ¹¹	1,024 × 768 pixels* ¹²	
Scanning frequency	SDI			
SDI	SD-SDI* ¹³ /HD-SDI* ¹⁴ /3G-SDI* ¹⁵			
HDMI/DVI-D/DIGITAL LINK	480i* ¹⁶ , 576i* ¹⁶ , 480p, 576p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/24p, 1080/24sF, 1080/25p, 1080/30p, 1080/60p, 1080/50p VGA (640 × 480)–WUXGA* ¹⁷ (1,920 × 1,200), compatible with non-interlaced signals only, dot clock: 25–162 MHz			
RGB YPbPr (YCbCr)	fh: 15.75 kHz, fv: 60 Hz [525i (480i)] fh: 31.50 kHz, fv: 60 Hz [525p (480p)] fh: 15.63 kHz, fv: 50 Hz [625i (576i)] fh: 31.25 kHz, fv: 50 Hz [625p (576p)] fh: 45.00 kHz, fv: 60 Hz [750 (720)/60p] fh: 15.75 kHz, fv: 60 Hz [NTSC/NTSC4.43/PAL-M/PAL60], fh: 15.63 kHz, fv: 50 Hz [PAL/PAL-N/SECAM]	fh: 37.50 kHz, fv: 50 Hz [750 (720)/50p] fh: 33.75 kHz, fv: 60 Hz [1035/60i] fh: 33.75 kHz, fv: 60 Hz [1125 (1080)/60i] fh: 28.13 kHz, fv: 50 Hz [1125 (1080)/50i] fh: 28.13 kHz, fv: 25 Hz [1080/25p]	fh: 27.00 kHz, fv: 24 Hz [1080/24p] fh: 27.00 kHz, fv: 48 Hz [1080/24sF] fh: 33.75 kHz, fv: 30 Hz [1080/30p] fh: 67.50 kHz, fv: 60 Hz [1080/60p] fh: 56.25 kHz, fv: 50 Hz [1080/50p]	
Video/YC				
Optical axis shift	V: +50 %, H: ±10 % (powered)	V: +60 %, H: ±10 % (powered)	V: +50 %,* ¹⁸ H: ±10% (powered)	
Keystone correction range	V: ±40° (±30° with the ET-DLE055/DLE085)			
Installation	Ceiling/floor, front/rear, portrait* ¹⁹			
Terminals	SDI IN DVI-D IN HDMI IN RGB 1 IN RGB 2 IN VIDEO IN 3D SYNC IN/OUT 3D SYNC OUT SERIAL IN SERIAL OUT REMOTE 1 IN REMOTE 1 OUT REMOTE 2 IN LAN / DIGITAL LINK	BNC × 1 (3G/HD/SD-SDI) – DVI-D 24-pin × 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only) HDMI 19-pin × 1 (Deep Color, compatible with HDCP) BNC × 5 (RGB/YPbPr/YCbCr/YC × 1) D-Sub HD 15-pin (female) × 1 (RGB/YPbPr/YCbCr × 1) BNC × 1 (composite video) BNC × 1 (3D timing signal) BNC × 1 (3D timing signal) D-sub 9-pin (female) × 1 for external control (RS-232C compliant) D-sub 9-pin (male) × 1 for link control M3 × 1 for wired remote control M3 × 1 for link control (for wired remote control) D-sub 9-pin (female) × 1 for external control (parallel) RJ-45 × 1 (for network and DIGITAL LINK (video/audio/network/serial control) connection, 100Base-TX, compatible with PLink™)		
Cabinet materials	Molded plastic			
Dimensions (W × H × D)	PT-DZ870/DW830/DX100: 498 × 200* ²⁰ × 556 mm (19-19/32 × 7-7/8* ²⁰ × 21-7/8 in) (with supplied lens) PT-DZ870L/DW830L/DX100L: 498 × 200* ²⁰ × 513 mm (19-19/32 × 7-7/8* ²⁰ × 20-3/16 in) (without lens)			
Weight* ²¹	PT-DZ870/DW830/DX100: Approx. 20.0 kg (44.1 lbs) (with supplied lens); PT-DZ870L/DW830L/DX100L: approx. 19.2 kg (42.3 lbs) (without lens)			
Operating environment	Operating temperature: 0 °C–45 °C (32 °F–113 °F)* ²² , operating humidity: 20%–80% (no condensation)			
Applicable software	Logo Transfer Software, Multi Projector Monitoring & Control Software Upgrade kit (ET-UK20)			
Supplied accessories	Power cord with secure lock, wireless/wired remote control unit, batteries (R6/LR6/AA type × 2), software CD-ROM (Logo Transfer Software, Multi Projector Monitoring & Control Software) (× 1)			

Optional accessories

Zoom lens

ET-DLE085 **NEW**
ET-DLE150
ET-DLE250
ET-DLE350
ET-DLE450

Ceiling mount bracket

ET-PKD120H (for high ceilings)
ET-PKD120S (for low ceilings)

Attachment for ceiling mount bracket

ET-PAD120

Fixed-focus lens

ET-DLE055

Replacement lamp unit

ET-LAD120
ET-LAD120W (Twin Pack)

Upgrade kit

ET-UK20
(Geometry Manager
Pro included)

Replacement lamp unit for portrait mode

ET-LAD120P
ET-LAD120PW (Twin Pack)

Smoke-resistant filter

ET-SFD120

*⁸ When the STANDBY MODE is set to ECO, network functions such as power on over the LAN will not operate. Also, only certain commands can be received for external control using the serial terminal. *⁹ 1.27–5.08 m (50–200 in) with the ET-DLE055. *¹⁰ Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. *¹¹ Input signals that exceed this resolution will be converted to 1,280 × 800 pixels. *¹² Input signals that exceed this resolution will be converted to 1,024 × 768 pixels.

*¹³ SMPTE ST 259 compliant, [YCbCr 4:2:2 10-bit] 480i, 576i. *¹⁴ SMPTE ST 292 compliant, [YCbCr 4:2:2 10-bit] 720/50p, 720/60p, 1035/60i, 1080/50i, 1080/60i, 1080/25p, 1080/24p, 1080/24sF, 1080/30p. *¹⁵ SMPTE ST 424 compliant, [YPbPr 4:2:2 10-bit] 1080/50p, 1080/60p, [RGB 4:4:4 12-bit/10-bit] 1080/50i, 1080/60i, 1080/25p, 1080/24p, 1080/24sF, 1080/30p. *¹⁶ Supports signals with a 27 MHz dot clock (pixel repetition) only. *¹⁷ WUXGA resolution is supported only when the signals are compliant with VESA CVT-RB (Coordinated Video Timing-Reduced Blanking). *¹⁸ +45% from center of screen with the E T-DLE085. *¹⁹ Requires optional lamp units for portrait mode. *²⁰ With legs at shortest position. *²¹ Average value. May differ depending on the actual unit. *²² The operating temperature range is 0 °C to 40 °C (32 °F to 104 °F) when the high altitude mode is set to on (for altitudes from 1,400 m to 2,700 m (4,593 ft to 8,858 ft) above sea level). Also, if the ambient temperature exceeds 40 °C (104 °F) (35 °C (95 °F) in high altitude mode) when the projector is being used with lamp select set to dual and lamp power set to normal, the light output may be reduced approximately 20 % to protect the projector.

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The projection distances and throw ratios given in this leaflet are for use only as guidelines. For more detailed information, please consult the dealer from whom you are purchasing the product. The PLink trademark is an application trademark in Japan, the United States, and other countries and regions or registered trademarks. RoomView, Crestron RoomView, and Crestron Connected are trademarks of Crestron Electronics, Inc. AMX is a trademarks of AMX, LLC registered in the U.S. and other countries. All other trademarks are the property of their respective trademark owners. Projection images simulated. © 2013 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Web Site – panasonic.net/avc/projector
Facebook – www.facebook.com/panasonicprojector
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of January 2013.

PT-DZ870PRE1 Printed in Japan.